



Model 90A Annunciator

FOR POWER GENERATION, TRANSMISSION & DISTRIBUTION, PETROLEUM, PETROCHEMICAL, AND OTHER PROCESS INDUSTRIES



INNOVATIVE ANNUNCIATOR

Based on the highly acclaimed SERIES 90, AMETEK's new SERIES 90A Annunciator brings alarm monitoring to new levels. It has several communication options, can provide time stamped alarms and all features and options are field configurable. Installation and setup have been simplified making this an ideal fit for new projects or system replacements. The unique software configuration provides more features and functions a mouse click away.



Communications

Transmit or receive alarms using our RS-232/485 serial or Ethernet port. The SERIES 90A supports Modbus and DNP protocols. Communicate via OPC using our OPC Server Software.

Compact Size

The Annunciator and all electronics including the communication options are self contained within a compact frame less than 7 inches deep. In most cases, the power supply is included inside the system simplifying installation and wiring.

Time Stamped Alarms (SER)

All of your alarms can include a timestamp and can be synchronized by IRIG-B or our internal clock. This can be presented through Modbus, DNP, OPC or to a local printer or terminal for viewing. Connect this to your Alarm Management Software for advanced notifications of your critical alarms.

Flexible Design

The window legends are printed on standard transparency film, making it easy to change legends at any time. The Annunciator capacity can be increased with built-in expansion. All features and options are field selectable and upgradeable.

Software Configuration

While all systems are pre-configured to your specifications, the software configuration tool unleashes the true power of the SERIES 90A.

You can select any operational sequence, sort alarms by group, configure your relay outputs and more. There is never any reason to pull out the front accessible input cards as changes can be made via software.

Reliability

Every SERIES 90A Annunciator is equipped with low power, long life LED's. The brightness exceeds standard incandescent bulbs and they last years longer. If a LED needs replacement, our automatic detector provides notice so critical alarms are not missed. A built-in ground fault detector is available for indicating ground faults in your field wiring.

FEATURES AND BENEFITS

- Serial & Ethernet Communications: Modbus, DNP, OPC Protocols
- Compact Size
- Timed Stamped Alarms (SER)
- Software Configurable
- LED Illumination (Standard)
- Laser Printed Legends
- Internal Self Diagnostics

AMETEK[®]

**POWER
INSTRUMENTS**

Experience the Power™

SPECIFICATIONS

INPUT

Field Contacts

- Normally Open (N.O.) or Normally Closed (N.C.) input selection through software or hardware
- Wetted (voltage supplied) or dry (voltage free) contacts

Field Contact Voltage

- 12, 24, 48, 125 VDC, 120 VAC jumper selectable (.0018mA per input)

Input Isolation

- Each input is optically isolated

Input Response

- 50 milliseconds (standard)
- 1 millisecond fast response (opt)
- 50 milliseconds to 250 seconds software adjustable

DISPLAY

LED

- White LED, minimum 2 per window

Window Sizes (h x w)

- Quad: .75 x .75 inch (19 x 19 mm)
- Third: 1.0 x 3.0 inch (25 x 76 mm)
- Half: 1.5 x 3.0 inch (38 x 76 mm)
- Full: 3.0 x 3.0 inch (76 x 76 mm)

Window Color

- White, red, yellow, amber, green, blue

Legends

- Laser printed on transparency film or engraved windows

ALARM SEQUENCE

Sequence Selections

- LN, AO, AONL, AF, AFNL, FR, AM, FRM, AS, ASFR, ASFRM, TFS, TFSFRM, TFSM, ARR, FRR, VS, VSRR, MC
- Software configurable
 - Dual color sequences
 - Customized flash rates
 - Up to 4 first out groups

CONTROLS

- Integral test, acknowledge, silence and reset with LED status lights
- External push button inputs
- Configurable switch inputs (inhibit LEDs, horns, relays)

OUTPUTS

Auxiliary Relay Option

- Individual or dual relay per point
- Follows field contact or alarm sequence
- Software configurable
- Energized/de-energized operation
- Form A or form B (N.O. or N.C.)
- Form C (SPDT)

Common Relays

- 2 relays included for: critical and non-critical horn; ringback audible
- 2 relays available for: critical and non-critical reflash, common alarm; watchdog, power fail, ground fault
- Software configurable
- Energized or de-energized operation
- Form A or form B (N.O. or N.C.)

Relay Ratings

- 24 VDC @ 5.0 amps
- 110 VDC @ 0.1 amps
- 120 VAC @ 5.0 amps

Audible

- Internal 80db @ 30cm audible device external horns available

COMMUNICATION

Serial Modbus

- Master or slave
- Transmit or receive alarms
- RS-232/485 or Ethernet
- Pushbutton controls

DNP 3.0

- Slave mode
- Transmit alarms
- RS-232/485 or Ethernet
- Pushbutton controls

OPC Server Software

- Ver. 2.0 OPC DA

Serial ASCII

- RS-232/485 or Ethernet
- For local terminal/printer

TIME STAMPED ALARMS

- < 5 msec resolution across all inputs
- IRIG-B time sync input or internal clock
- Point #, alarm status, time and date
- Modbus, DNP, ASCII outputs
- 500 event storage

CONNECTIONS

Input/Output Terminals

- Fixed barrier terminal block, 12 GA (2.5mm) maximum, ring, spade or bare wire termination.

Communication Ports

- Serial: 9 pin female D connector
- Ethernet: RJ45 connector
- IRIG-B: BNC connector

POWER REQUIREMENTS

Internal or External Power Supplies

- 230 VAC (176-264 VAC 50 Hz)
- 120 VAC (88-132 VAC 60 Hz)
- 125 VDC (100-250 VDC)
- 48 VDC (38-58 VDC)
- 24 VDC (19-29 VDC)

Max. 1.7 watts/input @ power input

MECHANICAL

Mounting

- Semi-flush panel mounting
- 19 inch rack mounting
- Wall (surface) mounting
- NEMA enclosures

Weight

- 1.2 lbs per cell (0.34 kg per cell)

ENVIRONMENT

Operating Temperature Range:

- -4 to 122°F (-20 to 50°C)

Humidity:

- 20-95% RH

Surge Withstand:

- ANSI C37.90.1 (oscillatory)

Fast Transient:

- IEC-61000-4-4

Surge Immunity:

- IEC-61000-4-5

EMI/RFI/ESD:

- IEC-61000-4-3, 4-6, 6-3, 4-8, 4-2

Isolation:

- 1950 VDC or 1400 VAC input to output, logic, case

CERTIFICATIONS

UL, ULC, CE, and FM Class 1, Div 2

Semi-flush Mounting Details inches (mm)

Cells H or W	Over All Ht. or Wt.	Panel Cut-Out Ht. or Wt.
1	5.0 (127)	4.06 (103)
2	8.47 (215)	7.53 (191)
3	11.94 (303)	11.00 (279)
4	15.40 (391)	14.47 (368)
5	18.88 (479)	17.94 (456)
6	22.34 (568)	21.41 (544)
7	25.81 (656)	24.88 (632)
8	29.28 (744)	28.34 (720)
9	32.75 (832)	31.81 (808)
10	36.22 (920)	36.28 (896)
11	39.69 (1008)	39.75 (1010)
12	43.16 (1096)	43.22 (1098)
13	46.63 (1184)	46.69 (1186)

Depth Behind Panel: 6.75", 8" with Rear Cover

Example: 2 H x 3 W has a cut-out height of 7.53 (191) and a cut-out width of 11.0 (279)



For customer support call:

POWER INSTRUMENTS

1725 Western Drive
West Chicago, IL 60185
Tel: 630.231.5900
Fax: 630.231.4502
power.industrial@ametek.com

HEADQUARTERS

AMETEK Power Instruments
50 Fordham Road
Wilmington, MA 01887
Tel: 978.988.4903
Fax: 978.988.4990
www.ametekpower.com
power.industrial@ametek.com

EUROPEAN HEADQUARTERS

Unit 20, Ridgeway
Donibristle Industrial Estate
Dalgety Bay, Dunfermline, KY119JN
Scotland U.K.
Tel: 44.1383.825630
Fax: 44.1383.825715
sales@ametekuk.com

ASIA PACIFIC HEADQUARTERS

10 Ang Mo Kio Street 65
#05-12 Techpoint
Singapore 569059
Tel: 65.6484.2388
Fax: 65.6481.6588



ISO 9001 Certified