



# DPMS Transducer Digital Power Measurement System

FOR CONTROL, MONITORING, AND DATA ACQUISITION



## DPMS TRANSDUCER

AMETEK's Digital Power Measurement System (DPMS) transducer can make multiple measurements simultaneously with its direct communication capability. The advance technology of the DPMS replaces traditional transducers that require one transducer for each measurement.

The DPMS can be configured to the exact measurement you need. Configuration is done easily with DPMSTalk configuration software. The DPMS makes an excellent back up strategy. Rather than stocking numerous types and quantities of backup transducers, you can now stock far fewer DPMS units, which can be quickly and easily configured to your replacement needs. With MODBUS and DNP as standard protocols, connections have never been simpler. The RS-485 port allows the transducer to communicate directly to your equipment through a multi-drop configuration, saving you valuable input ports and the need for multiplexors. Also included is a separate port to use with the DPMS-D optional external digital display. Not only is it easier for engineering, the DPMS will also save on wiring and valuable panel space.



## FEATURES AND BENEFITS

- Programmable as 2, 2.5 or 3 elements
- Configurable analog and digital contact and alarm outputs
- Programmable built-in communications of MODBUS and DNP 3.0
- Remote display option available
- Transformer Loss Compensation (TLC)

### DPMS-D (Optional Digital Display)

- Communicates with 15 DPMS units via RS-485 without loss of serial communications
- 3 key switches allow selection of data or unit to be viewed
- Maximum distance is 4000 feet
- 12 standard and 4 custom display screens
- Displays in primary units (CT and PT) ratios configured in DPMS

### DPMS Ordering Information

TYPICAL MODEL NUMBER (coded by color)

DPMS -P1 -C5 -A1 -D0 -R0

#### Code Description

DPMS Digital Power Measurement System

#### Nominal Voltage

P1 = 120V      P3 = 480V  
P2 = 277V      P4 = 69V

#### Nominal Current

C5 = 5A

#### Analog Output

A0 = No Analog      A2 = 4-20 mA  
A1 = 0 ± 1 mA

#### Digital Output

D0 = No Contacts  
D1 = Contact Outputs/KYZ

#### Programming Kit

R0 = No Kit  
R1 = Kit with DPMS Talk Software and Cable



## SPECIFICATIONS

### PROGRAMMABLE CONFIGURATION

- 2 element for 3-phase 3-wire delta
- 2-1/2 element for 3-phase 4-wire wye
- 3 element for 3-phase 4-wire wye

### MEASURED AND/OR CALCULATED QUANTITIES

- Watts/Vars/VA
  - Per phase and total
- Voltage
  - Phase to neutral, phase to phase
- Current
  - Phase and neutral (calculated)
- Power Factor
  - Per phase and system
- Frequency
  - Total harmonic distortion of each voltage and current
- Watthours/Varhours
  - Delivered and received

### INPUTS

- Current Nominal
  - 5 amps
- Operating Range
  - 0 to 10 amps
- Burden per Element
  - 0.25 VA
- Voltage
  - 120 volts Nominal
  - Range: 85 to 150 V
- Optional Voltages
  - 69 VAC Nominal, Range 50-85 VAC
  - 277 VAC Nominal, Range 180-320 VAC
  - 480 VAC Nominal, Range 310-550 VAC
- Burden per Element
  - 0.05 VA
- Frequency
  - 45 to 65 Hertz
- Sample Rate
  - 128 Samples/Cycle
- Power Supply
  - 95 to 265 VAC @ 50/60 Hz or DC
  - 6 VA Maximum @ 120 V

### OPTIONAL OUTPUTS

- 3 Channel Analog
  - Independently Configured and scaled with DPMSTalk
- Option A1
  - 0 to  $\pm 1$  mA, maximum 10 V compliance
- Option A2
  - 4 to 20 mA, maximum 12 V compliance
- Response Time
  - $\leq 200$  mS
- 6 Channel Digital (KYZ) Option D1
  - Independently configured and scaled with DPMSTalk for energy measurements or as high/low threshold alarms. Solid-state rated 50 mA @135 VAC/VDC with less than 5 V drop 54,000 CPH maximum.

### MEASUREMENT/ CALCULATION ACCURACY

- Volts, Amps, Watts, Vars
  - 0.2%
- Watthours, Varhours
  - 0.2%
- Neutral Current
  - 0.75%
- Volt Amps
  - 0.5%
- Power Factor
  - $\pm 0.008$  (rated VA/input VA)
- Analog output
  - $\pm 0.1\%$

### MECHANICAL

- Size
  - 3.75 in. x 5.375 in. x 6.5 in. (95.25 mm x 136.525 mm x 165.1 mm)
- Weight
  - 2.6 lbs (1.2 kg)
- Communications Hardware
  - RS-232 (full duplex) or RS-485 (half duplex)
- Programmable Protocols
  - Modbus: RTU or ASCII Mode
  - DNP 3.0

### ENVIRONMENT

- Operating Temperature Range:
  - 4° to 158°F (-20° to 70°C)
- Surge Withstand
  - ANSI/IEEE C37.90, IEC 801-4 Class 4
- Isolation
  - 2500 VAC RMS from input/output/power/case
  - 500 VAC RMS between digital outputs

### DPMS-D OPTIONAL DIGITAL DISPLAY

- 4 line x 20 character vacuum fluorescent display allows Unit ID and 3 simultaneous measurements to be viewed
- Character height 0.19 inch
- Displays in primary units (CT and PT ratios configured in DPMS)
- All Measured Quantities available for display Communications
  - Multi-addressing allows communication to up to 15 DPMS units per DPMS-D display module
  - Half duplex RS-485
  - Recommended maximum distance between DPMS and DPMS-D is 4000 feet
- Power Requirements
  - 95 to 265 VAC @ 50/60 Hz or DC
- Mechanical Panel Cutout
  - 4.38 in. x 3.75 in. (111.25 mm x 95.25 mm)
- Weight
  - 1.4 lbs (0.64 kg)
- Operating Temperature Range
  - 4° to 158°F (-20° to 70°C)
- Surge Withstand
  - ANSI/IEEE C37.90, IEC 801-4 Class 4
- Isolation
  - 2500 VAC RMS from power to case or communications port1
- A portion of the DPMS product was funded by the New York State Energy Research and Development Authority (NYSERDA).



For customer support call:

**POWER INSTRUMENTS**  
255 North Union Street  
Rochester, NY 14605  
Tel: 585.263.7700  
Fax: 585.454.7805  
power.industrial@ametech.com

**HEADQUARTERS**  
AMETEK Power Instruments  
50 Fordham Road  
Wilmington, MA 01887  
Tel: 978.988.4903  
Fax: 978.988.4990  
power.industrial@ametech.com

**EUROPEAN HEADQUARTERS**  
Unit 20, Ridgeway  
Donibristle Industrial Estate  
Dalgety Bay, Dunfermline, KY119JN  
Scotland U.K.  
Tel: 44.1383.825630  
Fax: 44.1383.825715  
sales@ametechuk.com

**ASIA PACIFIC HEADQUARTERS**  
10 Ang Mo Kio Street 65  
#05-12 Techpoint  
Singapore 569059  
Tel: 65.6484.2388  
Fax: 65.6481.6588



ISO 9001 Certified