

# JEMSTAR High Accuracy Revenue Meter

FOR GENERATION, TRANSMISSION, AND INDUSTRIAL POWER MEASUREMENT



## REVENUE METER

High precision and ease of use best describes the JEMSTAR revenue meter. Quick intuitive setup using Windows based software makes configuration a breeze. For revenue and billing, the JEMSTAR's high accuracy guarantees that every measurement is properly accounted for. Anticipate loads in advance with our demand prediction option. Our advanced communication options provide many choices and protocol platforms for easy access to our metering data. For peace of mind, your site conditions are continuously monitored with our diagnostic tools that notify you quickly of any impending problem.

### **Ease of Use**

The JEMSTAR is the easiest meter to configure with its Windows based JEMWARE Configuration Wizard and on-line help system. The quick intuitive process eliminates the need for specialized training and gets you up and running with minimal effort. The JEMSTAR meter is user friendly with its built-in menu-driven display and site verification tools.

### **High Accuracy**

The JEMSTAR has a guaranteed accuracy of 0.07% on Watt-hours with an unprecedented typical accuracy of 0.03%. When accounting for revenue, even a fraction of a percent can mean the difference of thousands of dollars. Accuracy is further enhanced with TLC, LLC and selectable gain adjustments on PT's and CT's.

### **Power Quality**

The JEMSTAR records voltage sag & swells based on configurable thresholds so you can determine the quantity, severity and location of your power quality disturbances. In addition, the JEMSTAR logs current/voltage THD, power factor, imbalance and frequency so you have the complete picture on power quality.

### **Site Diagnostic Tools**

You will be notified automatically of site and diagnostics problems from configured threshold settings and system status diagnostics including Phone Home on Power Failure.

### **Advanced Communication**

Many communication choices are available with RS-232, RS-485, internal modems and optical probes.



Simultaneous communications are possible using industry standard protocols: DNP 3.0, Modbus RTU and ASCII, ANSI Tables, JEM Binary and support for MV90.

## FEATURES AND BENEFITS

- Easy to Use
  - JEMWARE configuration wizard
  - On-line help system
  - Menu-driven graphical display
  - Site verification tools
- High Accuracy
  - 0.07% of reading for watt-hours
  - Simultaneous uncompensated and compensated (TLC, LLC) measurements
  - Selectable PT/CT gain error correction
- Versatile
  - Power quality, totalization
  - Digital inputs/outputs, analog outputs
  - Wide, auto-ranging input (55-530 VAC)
- Advanced Communication Options
  - Internal modem
  - Single RS-232/485 (selectable)
  - Dual RS-232/485 (simultaneous)
  - Modem and RS-232/485

**AMETEK®**

**POWER  
INSTRUMENTS**

Experience the Power™

## SPECIFICATIONS

### METER FORMS

Meter Forms: 5,6,8,9

### INPUTS

#### Voltage

- 55-530 VAC auto-ranging
- Burden\*: 0.5 VA @ 530V  
\*Does not include auxiliary power requirements.

#### Current

- 1 Amps: ANSI Class 2
- 5 Amps: ANSI Class 10
- 10 Amps: ANSI Class 20
- Burden: 0.5 VA maximum
- Overload: 1.5x rated class current continuous, 20x rated class current for 0.50 sec
- Frequency range: 45-55 Hz, 55-65 Hz

### AUXILIARY POWER

55 – 530 VAC, 90 – 250 VDC

#### S-base and A-base

- Normally derived from A-phase voltage input

#### Switchboard

- Separate terminals, AC or DC

#### Auxiliary Power Burden

- 15 VA max

### ACCURACY

#### Watt-hour

- 0.07% Reading (0.03% Typ.)

#### Clock

- Synchronized to line or  $\pm 3$  minutes per month maximum error for internal reference.

#### Loss Compensation

- Transformer Loss Compensation (TLC) and Line Loss Compensation (LLC)
- PT and CT Error Gain Correction

### MEASUREMENTS

#### Energy PolyPhase Quantities

- Watthour, VARhour, VAhour, Amphour, Qhour

#### Energy Per Phase Quantities

- Watthour, VARhour, VAhour, Amphour, Qhour

#### Instantaneous Quantities

- Per phase:  $\pm$  Watts,  $\pm$ VARs, Quadrant Vars,  $\pm$ VA,  $\pm$ Q, PF, Volts, Volts THD, Amps, Neutral Current, Amps THD, Volts<sup>2</sup>, Amps<sup>2</sup>
- System:  $\pm$ Watts,  $\pm$ VARs, Quadrant Vars,  $\pm$ VA,  $\pm$ Q, PF, Volts, Amps, Amps<sup>2</sup>, average volts, frequency

### REGISTERS

50 Normal, 50 Alternate, 50 Test

#### Demand Registers

- Fixed or sliding window
- Interval length: 1-60 minutes

### LOAD PROFILE

4 channels of storage (standard)  
12 channels of storage (optional)

#### Programmable Interval

- 1-60 minutes

45 days storage using four channels at 15-minute intervals

### TOTALIZATION (OPTIONAL)

Up to 2 contact inputs

Up to 12 totalization measurements displayed and recorded

### POWER QUALITY (OPTIONAL)

Configurable thresholds for voltage sags and swells per phase

Records start & duration in cycles

Records min/max/avg voltage and current per phase, avg power factor

Stores up to 100 events

Maximum event length of 600 cycles

### DIGITAL INPUTS/OUTPUTS (OPTIONAL)

DI/DO option: Two Form-A contact inputs and four Form-A solid-state outputs

5 KYZ option: Two Form-A contact inputs and five Form-C solid-state outputs  
(only one option available at a time)

#### Contact Inputs

- Maximum voltage 40 VDC
- User-configurable for: Pulse counter, interval synchronization pulse, TOU rate override, status input, totalization

#### Solidstate Outputs

- Maximum open-circuit voltage: 200V DC or peak AC
- Maximum switching current: 50 mA
- User-configurable for: any consumption quantity, energy pulse (KYZ), site monitor alarm, threshold alarm, demand sync, voltage sag/swell alarm, system error alarm

### ANALOG OUTPUTS (OPTIONAL)

- Three independent outputs 0  $\pm$ 1 mA or 4-20 mA  
*\*not available with 5 KYZ option*
- User-configurable for any instantaneous quantity

### COMMUNICATIONS

#### Optical Port (Standard)

- Type 2 – 19,200 Baud
- RS-232 & RS-485 (Optional)
- User configurable: 300 to 38400 baud

#### Internal Modem (Optional)

- User configurable: 300 to 14400 baud

Call-Home on Power Outage Modem (Optional)

Modem/RS-485 CR (Communication Repeater) (Optional)

#### Protocols

- Modbus ASCII or RTU (optional)
- DNP 3.0 (optional)
- ANSI Tables (optional)
- JEM Binary (standard)
- IEC 870-5-102 (standard)

### MECHANICAL

#### Case Styles

- Socket connected (S base), small switchboard case, bottom connected (A-Base), meter retrofits (JEM-2 and others)

#### Size and Weight

- S base: 5.5 pounds
- A-base: 7.5 pounds
- Switchboard case: 11.5 pounds

### ENVIRONMENT

#### Operating Temperature

- -40° to 185°F (-40° to 85°C)

#### Storage Temperature

- -40° to 185°F (-40° to 85°C)

#### Humidity

- 5 to 95% relative humidity, non-condensing

#### Surge Withstand (SWC)

- ANSI Standard C37.90.1-1989, ANSI Standard C62.41

#### Fast Transient

- IEC Standard 687 Section 5.5.4

### STANDARDS

#### Agency Standards and Certifications:

- ANSI Standard C12.16-1991
- ANSI C12.20-1998 Accuracy 0.2%
- IEC Standard 687 Class 0.2
- FCC Part 68, FCC Part 15
- IEC 60687
- CE
- Measurement Canada
- California ISO
- NY PSC



For customer support call:

#### POWER INSTRUMENTS

255 North Union Street  
Rochester, NY 14605  
Tel: 585.263.7700  
Fax: 585.454.7805  
power.industrial@ametek.com

#### HEADQUARTERS

AMETEK Power Instruments  
50 Fordham Road  
Wilmington, MA 01887  
Tel: 978.988.4903  
Fax: 978.988.4990  
power.industrial@ametek.com

#### EUROPEAN HEADQUARTERS

Unit 20, Ridgeway  
Donibristle Industrial Estate  
Dalgety Bay, Dunfermline, KY119JN  
Scotland U.K.  
Tel: 44.1383.825630  
Fax: 44.1383.825715  
ametek@ametekuk.com

#### ASIA PACIFIC HEADQUARTERS

10 Ang Mo Kio Street 65  
#05-12 Techpoint  
Singapore 569059  
Tel: 65.6484.2388  
Fax: 65.6481.6588



ISO 9001 Certified